

Verint SmartSight S1708e

High-Resolution 8-Input Ethernet Video Server



The Verint SmartSight® S1708e Ethernet video server is designed for high-resolution video monitoring and surveillance applications in which a high concentration of cameras terminates within the same area.

The S1708e delivers 4CIF, 30 frames per second (fps), MPEG-4-based video over 10/100Base-T networks using cat 5, fiber optic, and wireless media. The S1708e can be extended over Local and Wide Area Networks (LANs and WANs) or the Internet using ISDN, PSTN, or xDSL routers.

The Verint solution's compact design accommodates eight video inputs within a 1U, 6 inch (15 cm) depth enclosure. Multiple units can be rack mounted on one or both sides of a standard 19 inch (48 cm) cabinet.

The S1708e is available in two configurations: a video encoder (S1708e-T) with eight analog video inputs at 30 fps each and a video encoder (S1708e-T-A) with eight analog video inputs at 30 fps each with bidirectional audio.

Configuration and management are made easy with Verint nDVR™, Loronix Video Manager®, or SConfigurator software.

- ✓ Compact footprint: eight input video streams in 1U enclosure
- ✓ MPEG-4-based video input
- ✓ High-resolution, 4CIF video streaming at 30 fps for each input
- ✓ Scalable resolution from 176 x 128 to 704 x 480 NTSC pixels (176 x 144 to 704 x 576 PAL pixels)
- ✓ All firmware upgradeable via the network (including the video codec)
- ✓ User selection of RTP/IP, UDP/IP, TCP/IP, or multicast streaming
- ✓ SSL-based user authentication
- ✓ RS-232 serial port for integration to access control systems
- ✓ RS-422/485 serial port to support motorized domes and cameras
- ✓ Eight discrete alarm inputs and two relay outputs
- ✓ Video loss alarm
- ✓ Optional bidirectional audio interface supporting microphone or line-level input, and headphone or line-level output

The Verint SmartSight S1708e is a powerful solution for organizations that seek DVD-quality images with high frame rates and a lower cost per port.



NETWORK

Interface	Ethernet 10/100Base-T
Connector	RJ-45 jack
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, or multicast IP Others: DNS and DHCP client
Security	SSL-based authentication

VIDEO

Input	8 composites, 1 Vpp into 75 ohms (NTSC/PAL)
Connectors	BNC female connectors
Termination	75-ohm video termination per input
Compression	MPEG-4-based
Resolution	Scalable from 176 x 128 to 704 x 480 NTSC pixels (176 x 144 to 704 x 576 PAL pixels)
Frame rate	8 at 1-30 fps in NTSC (1-25 fps in PAL) programmable (full motion)
Bandwidth	Each stream is configurable between 30 kbps and 4 Mbps with a combined max throughput of 6 Mbps

SERIAL PORT

Electrical levels	Port 1: RS-232 (max. 230 kbps) Port 2: RS-422/485 2/4 wires (max. 230 kbps)
Connectors	Port 1: DB-9 Port 2: pluggable screw-terminal strip
Operating mode	Transparent serial port supporting any asynchronous serial protocol

ALARM AND AUDIO

Alarm	Input: 12 dry contacts Output: 2 relay contacts (48V AC/DC at 100 mA max.)
Bidirectional audio (optional)	Input: -46 to -3 dBV into 1 kOhm Output: -46 to -3 dBV into 16 ohms min.
Audio connectors	One set of 0.14 in. (3.5 mm) input and output stereo jacks

POWER

Supply voltage	12V DC +/- 10%
Consumption	22W (1.8A at 12V DC)

PHYSICAL

Enclosure	Metal case with flange mount (black color)
Size	17L x 6.1W x 1.7H in. (431.8L x 154.9W x 43.2H mm)
Weight	5.6 lb (2.6 kg)
Environmental	32°F to 122°F (0°C to 50°C)
Humidity	95% non condensing at 122°F (50°C)

MANAGEMENT

Configuration *	Remote: via nDVR, Loronix Video Manager, SConfigurator, or Telnet Local: via the serial port using any ASCII terminal
Firmware upgrade	Flash memory for upgrade of video codec and application firmware over the network

CERTIFICATION AND REGULATION

Canada	ICES-003/NMB-003
USA	FCC part 15 (subpart B, class A)
Europe	CE marked, EN 55022:1998 class A, EN 55024

WARRANTY

	3-year limited warranty, covering parts and labor
--	---

ORDERING

Part number	S1708e-T
Description	High-resolution Ethernet video server encoder with 8 inputs
Part number	S1708e-T-A
Description	High-resolution Ethernet video server encoder with 8 inputs and audio

OPTIONAL ACCESSORIES

Part number	PDP10
Description	19-inch (48-cm) power distribution panel rack mount. Supports up to ten S1708e encoders
Part number	PS1260
Description	110V AC to 12V DC power supply for a single unit
Part number	PS1280
Description	High capacity power supply for rack mount installations (to be used with PDP10)

* Product capabilities are enabled through software.

Verint. Powering Actionable Intelligence.™

Verint Systems (NASDAQ: VRNT) is a leading global provider of analytic software-based solutions for communications interception, networked video, and business intelligence. Verint solutions transform voice, video, and text into actionable intelligence — timely, mission-critical insights for achieving strategic goals.

Since 1994, Verint has been committed to developing innovative solutions that help our customers achieve their strategic objectives. Today, more than 1000 organizations in over 50 countries use Verint's actionable intelligence solutions to enhance security, boost operational efficiency, and fuel profitability.

By providing this document, Verint Systems is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Verint, Actionable Intelligence, BehaviorTrack, Dellis, HealthCheck, Lanex, Loronix, Loronix Video Manager, MotionTrack, microDVR, nDVR, netDVR, Powering Actionable Intelligence, SmartSight, Video Manager, and WebReview are trademarks of Verint Systems Inc., its subsidiaries or affiliates. All other registered trademarks, trademarks, and any associated logos are the properties of their respective owners.

© 2004 Verint Systems Inc. All rights reserved.

Email: videosales@verint.com
Or on the web at: www.verint.com/videosolutions
330 South Service Road, Melville, NY 11747 USA

